

REV.	DESCRIPTION	DATE
A	RELEASE	Sep. 17, 2003
B	DRAW MODIFY	Sep. 04, 2004
C	DRAW MODIFY	Oct. 21, 2004
D	DRAW MODIFY	Sep. 04, 2004
E	RoHS MODIFY	Feb. 04, 2005
F	DRAW MODIFY	Jan. 24, 2007
G	DRAW MODIFY	Jul. 25, 2007

$E = (\text{NO. OF POSITION PER ROW}) \times 2.54 + 1.02$   
 $(\text{NO. OF POSITION PER ROW}) \times 1.00 + .040$   
 $F = (\text{NO. OF POSITION PER ROW} - 1) \times 2.54$   
 $(\text{NO. OF POSITION PER ROW} - 1) \times 1.00$   
 $G = (\text{NO. OF POSITION PER ROW}) \times 2.54$   
 $(\text{NO. OF POSITION PER ROW}) \times 1.00$

## MATERIALS


1. HOUSING : P.P.S (UL 94V-0), BLACK.
2. TERMINAL : PHOSPHOR BRONZE. (t=0.60mm)
3. STRIP : P.P.S, BLACK.

## SPECIFICATION

1. CURRENT RATING : 1 AMP. MAX.
2. DIELECTRIC WITHSTANDING VOLTAGE :  
1000V AC R.M.S. FOR ONE MINUTE.
3. INSULATION RESISTANCE : 5000M OHMS MIN.  
AT 1000V DC.
4. CONTACT RESISTANCE : 30m OHMS MAX.
5. OPERATING TEMPERATURE : -40°C TO +85°C.

## ORDER INFORMATION :

25 - 12 01 - 2 \*\* - 2 G - R  
 SERIES CODE      TYPE 01      DUAL ROWS      ENVIRONMENTAL PROTECTION CODE (RoHS)      GOLD PLATING ON TAIL      10μ" GOLD PLATING ON CONTACT AREA      NUMBER OF POSITIONS PER ROW (32, 20, 4 PIN)

<u>TOLERANCE</u> .0=±0.30 [.012] .00=±0.20 [.008] .000=±.XXX .0000=±. ANG.=±3°		DRAWER		NAME POST HEADER RECEPTACLE 2.54mm PITCH, P.C.B. MOUNT PRESS FIT TYPE
		CHECK		
		APP'D		
		PRODUCT SPEC. _____		
				DRAW NO.
UNITS : mm [inch]				
SCALE NONE	SIZE A4	SHEET 1 OF 1	REV. G	10018

